

KWK RESISTORS INDIA



Programmable DC Electronic Load KELB180 Series - 1800W-2400W

KELB180 is a precision programmable DC electronic load controlled by a high performance microprocessor. It uses 3.5-inch TFT true color LCD display Offers 4-basic working modes (CC/CV/CR/CW) and 10 functional modes.

With comprehensive protection, over-heat protection, over-current protection, over-power protection, over-voltage protection, loop oscillation protection. KELB180 series E-load supports RS232, LAN, USB and analog interfaces to fit your versatile solution and testing needs.



Test Function

4 basic working modes CC/CV/CR/CW and 10 functional modes multiple extended function modes:

- ◆ Dynamic test mode (DYNA);
- ◆ OCP mode
- ◆ EFFECT mode
- ◆ Professional battery test function
- ◆ High-speed dynamic frequency conversion scanning function (SWEEP)
- ◆ AUTO mode
- ◆ Timing test mode.

Features

- ◆ 500 kHz high speed voltage, current sampling rate
- ◆ High precision voltage and current measurement
- ◆ Fast loop response speed and current slew rate
- ◆ Programmable single step up to 10μs
- ◆ Equipped with remote four –wire compensation
- ◆ Unique real-time display of current ripple and voltage ripple
- ◆ Real-time display of load power and resistance

Specifications

Model	KELB182		KELB182B		KELB242		KELB242B	
Input Voltage	15V	150V	50V	500V	15V	150V	50V	500V
Input Current	24A	240A	12A	120A	24A	240A	12A	120A
Input Power	1800W				2400W			
Min.operation voltage	1V@240A		5.5V@120A		1.5V@240A		4.5V@120A	
Min rise time@ FS current	60μs		60μs		60μs		60μs	
CV Mode								
Range	15V	150V	50V	500V	15V	150V	50V	500V
Resolution	0.2mV	2mV	0.7mV	7mV	0.2mV	2mV	0.7mV	7mV
Accuracy	±(0.05% + 0.025% FS)							
CC Mode								
Range	24A	240A	12A	120A	24A	240A	12A	120A
Resolution	0.3mA	3mA	0.1mA	1mA	0.3mA	3mA	0.1mA	1mA
Accuracy	±(0.1% + 0.1%FS)							
CR Mode								
Range	0.1Ω-75kΩ							
Resolution	16 Bits							
Accuracy	±0.1%							
CW Mode								
Range	1800W				2400W			
Resolution	16 Bits							
Accuracy	±(0.2% + 0.2%FS)							

KWK RESISTORS INDIA



Programmable DC Electronic Load KELB180 Series - 1800W-2400W

Dynamic mode								
Ta & Tb	10µs - 50s							
Min.resolution	10µs							
Min.rise time	3.2A/µs	0.8A/µs			3.2A/µs		0.8A/µs	
Read-back voltage								
Range	15V	150V	50V	500V	15V	150V	50V	500V
Resolution	0.1mV	1mV	0.3mV	3mV	0.1mV	1mV	0.3mV	3mV
Accuracy	±(0.025%+0.025%FS)							
Read-back current								
Range	24A	240A	12A	120A	24A	240A	12A	120A
Resolution	0.1mA	1mA	0.09mA	0.9mA	0.1mA	1mA	0.09mA	0.9mA
Accuracy	±(0.05% + 0.05%FS)							
Read-back Ripple								
Range (R/I)	500V / 120A							
Bandwidth	10Hz - 250kHz							
Accuracy	±1%							
Protection Range								
Over-power protection	1890W		1890W		2420W		2520W	
Over-current protection	252A		126A		252A		126A	
Over-voltage protection	158V		525V		158V		525V	
Over-temperature protection	=85°C							
Specification								
Dimension (L*W*D)	483mm x 428mm x 95mm							
Gross Weight	26 kgs				31 kgs			

Applications



KWK Resistors India Pvt. Ltd.

Reg. Office: B-81, Industrial Estate, Rajajinagar, Bengaluru-560044.India
 Works: #72, 3rd main, 2nd stage, Industrial suburb, Yeshwanthpur, Bengaluru-560022.India
 Ph.:+91-80-23370038, Tele/Fax:+91-80-23370046 Email: contact@kwk-resistors.in

